

## FIRST RE-ESTABLISHMENT

GCDB 140500

Quarter corner common to Sections 7 and 18, Township 39 South, Range 4 East, W.M.

At the corner, found projecting 8 inches, 2-inch diameter galvanized iron pipe, with 3-inch diameter standard BLM brass cap marked:

T39S R4E  
S7  
¼S —  
S18  
1966

An original bearing tree, marked by S. Truax in 1859:

- Now a fir snag, 35-inch diameter, scribed "¼S" in exposed upper face bears S11°W, 23.02 feet to scribed face. Record: 23.10 feet.

Bearing trees marked by the BLM in 1966 found:

- Sawed Fir stob, 18-inch diameter, scribed "¼S 18 BT" in exposed single face bears Record: S41°E, 47.52 feet to center.
- White Fir, 16-inch diameter, scribed "¼S 7BT" in exposed single face bears N4°W, 39.15 feet to center. Record: 38.94 feet.

Marked a new tree CS BT:

- White Fir, 7-inch diameter bears S55½°W, 54.60 feet to center of tree at lower blaze.

Corner lies at foot of (20%) east slope, about 40 feet north of spring branch c. N30°E and approximately 200 feet North of dirt road, c. N65°E and S70°W.

August 2, 1983  
R. Frost  
B. Malotte

Edward McGinty  
County Surveyor

V = 18°  
P.-75