

FIRST RE-ESTABLISHMENT

GCDB 200140

Quarter corner common to Sections 31 and 32, Township 39 South, Range 4 East, W.M. $V = 18^\circ$

In a found mound of stone, I set a $\frac{3}{4}$ x 8-inch re-steel rod, in a hole drilled 1 inch in bedrock, with a $2\frac{1}{2}$ -inch bronze disc marked:

Jackson County 1975
T39S R4E
 $\frac{1}{4}$ S
31 | 32

From which, original BTs recorded by S. Truax in 1859, found as follows:

- Juniper, 14-inch diameter, scribed "BT" in exposed lower face bears Record: $S55^\circ E$, 36.30 feet to scribed face.
- Juniper, 11-inch diameter, scribed " $\frac{1}{4}$ S" and "BT" in exposed faces bears Record: $S21^\circ W$, 76.56 feet to scribed lower face.
- **Note:** Both of the above trees have "W" nails in base.

I marked a new tree CS BT:

- Juniper, 11-inch diameter bears $S65^\circ W$, 152.20 feet to center of tree at lower blaze.

Corner lies 2 feet West of North-South fence and about 80 feet Southerly of location marker on 18-inch diameter Juniper, alongside road.

August 6, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor