

FIRST RE-ESTABLISHMENT

GCDB 200278

Closing Corner common to Sections 20 and 29, Township 39 South, Range 4 East, W.M. $V = 17^\circ$

From the following evidence, at the location described below, I set a 1 x 36-inch Galvanized iron pipe 3 inches in bedrock, with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
C.C. | 20

| 29

Original BTs recorded by P. Applegate in 1892, found as follows:

- Juniper, 19-inch diameter, scribed "T39S R4E S20" and "BT" in exposed faces bears Record: N34½°E, 39.60 feet, on slope, to scribed upper face. Re-measured, 38.51 feet to lower face. This is also the original SE BT of section corner 57.8 feet North.
- Juniper, 8-inch diameter, scribed "T39S R4E S29" and "BT" in exposed faces bears record, S36½°E, 71.28 feet to scribed lower face.
- A dead and down Juniper, 18-inch diameter, scribed "T39S R4E CC S20-29" and "BT" in exposed face, found at record location of SW BT.

I mounded stones around corner, deposited found original stone alongside as noted below, and marked a new tree CS BT:

- Juniper, 16-inch diameter bears S64°E, 86.32 feet to center of tree at lower blaze.

I found ⅝-inch diameter re-steel rod, projecting 28 inches in mound of stone, with aluminum cap marked:

Weyerhaeuser
T39S R4E
30 | 20

| 29
1970
O.R.L.S. 686

Bears S35°E, 3.00 feet. Reference, Survey No. 4754, dated 1971.

- The original 16 x 10 x 8-inch stone (recorded 20 x 12 x 8-inch) marked with 5 and 2 notches on adjacent sides, found among stones mounded around said 5/8-inch rod.
- BLM corner report (on file) notes original stone found disturbed in 1964.

Corner lies on top of rocky ridge encircled by large volcanic rocks.

August 11, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor