

**FIRST RE-ESTABLISHMENT**

**SECTION CORNER COMMON TO SECTIONS 19 AND 30 ONLY**

**GCDB 200300**

Section corner common to Sections 19 and 30, Township 39 South, Range 4 East, W.M.  $V = 17^\circ$

From the following evidence at the location described below:

I set a  $\frac{3}{4} \times 9\frac{1}{2}$ -inch re-steel rod, in a 3 inches deep, drilled hole in bedrock, with a  $2\frac{1}{2}$ -inch bronze disc marked:

Jackson County 1975  
T39S R4E  
19 |  
— |  
30 |

The two remaining original BTs recorded as Cedars by S. Truax in 1859 and noted as Junipers by P. Applegate in 1892, found as follows:

- Juniper, 13-inch diameter, containing scribe marks in upper and scribed "BT" in lower face bears record, on slope, to lower face,  $N27^\circ E$ , 40.26 feet. Re-measured 38.81 feet to scribed lower face.
- Juniper, 19-inch diameter, scribed "39 R4ES" and "BT" in exposed faces bears record,  $S43^\circ E$ , 34.98 feet on slope, to scribed upper face. Re-measured 33.68 feet to scribed upper face.
- This is also the original NE BT of the closing corner 57.8 feet South.

I mounded stones around corner and marked a new tree CS BT:

- Juniper, 13-inch diameter bears  $N67^\circ W$ , 71.15 feet to center of tree at lower blaze.

A found  $\frac{5}{8}$ -inch diameter re-steel rod, projecting 25 inches in mound of stone, with aluminum cap marked:

Weyerhaeuser  
T39S R4E  
19 |  
— | 20  
30 |  
1972  
O.R.S.S. 686

Bears  $S73^\circ W$ , 1.90 feet.

**Reference, Survey No. 4754, dated 1971.**

August 11, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor