

FIRST RE-ESTABLISHMENT

GCDB 240200

Quarter corner common to Sections 29 and 32, Township 39 South, Range 4 East, W.M. $V = 18^\circ$

From the following evidence, at the location described below, I lead a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
¼S
29
—
32

In a chiseled hole in bedrock.

Original BTs marked by S. Truax in 1859, found as follows:

- Black Oak shell, 14-inch diameter, 40 inches high, containing reverse impression of scribed "¼S BT" in single face bears $S14^\circ W$, 214.9 feet to said face. Record, $S14^\circ W$, 211.20 feet.
- Juniper, 23-inch diameter, scribed "BT" in exposed face bears record, $N34^\circ W$, 77.22 feet to scribed face, (erroneously recorded as a Cedar by Truax).

I mounded stones in ring around corner, and marked a new tree CS BT:

- Ponderosa Pine, 7-inch diameter bears $S14\frac{1}{2}^\circ W$, 186.3 feet to center of tree at lower blaze.
- A lead plug in the center of a chiseled cross on the apex of a 14 feet high (East face) rock outcrop bears $N54^\circ W$, 54.0 feet.

Corner lies 3.5 feet South of East-West fence line.

August 7, 1975
B. Malotte
K. Weaver

Approved by: Edward McGinty
County Surveyor