

FIRST RE-ESTABLISHMENT

GCDB 240600

Quarter corner common to Sections 5 and 8, Township 39 South, Range 4 East, W.M. $V = 20^\circ$

Found, original NE BT recorded by P. Applegate in 1893, now a down and decayed White Fir, about 20-inch diameter, scribed " $\frac{1}{4}$ S".

From the preceding evidence, I set a 1 x 36-inch Galvanized iron pipe 26 inches in the ground with a $2\frac{1}{2}$ -inch bronze disc marked:

Jackson County 1975
T39S R4E
 $\frac{1}{4}$ S 5
—
8

From which:

- The stump of the above-described original BT bears Record: $N22\frac{1}{4}^\circ E$, 28.38 feet to estimated lower face.
- The original SE BT is now gone.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- Cedar, 13-inch diameter bears, $N28\frac{1}{4}^\circ E$, 45.97 feet.
- Cedar, 14-inch diameter, with "W" nail in base bears $S20^\circ E$, 24.28 feet.

Corner lies in old skid trail (original stone not found) about 140 feet East of location marker on 14-inch diameter White Fir, located 90 feet East of road, C. NE.

August 14, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor