

FIRST RE-ESTABLISHMENT

GCDB 300200

Section corner common to Sections 28, 29, 32 and 33, Township 39 South, Range 4 East, W.M.
 $V = 20\frac{1}{2}^\circ$

Found, original NW BT marked by S. Truax in 1859, now a sawed Ponderosa Pine stump, 24-inch diameter, 5 feet high, scribed "T 4E S29" in opened upper face. Live tree now grows from burnt base.

From the preceding evidence:

I set a 1 x 36-inch Galvanized iron pipe 20 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975	
T39S	R4E
29	28
32	33

From which, the above-described original tree bears record, N31°W, 50.82 feet to estimated lower face.

- At record location of original SE Tree, scribed Pine remains are found.
- The original SW tree, now a dead and down I. Cedar, 14-inch diameter, scribed "T39S S32" and "BT" in exposed faces, has been moved by a tractor near corner into the SE quadrant.
- The NE BT is now gone.

I mounded stones around corner, marked new trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 9-inch diameter bears N23¼°E, 22.1 feet.
- Incense Cedar, 5-inch diameter bears S30¾°E, 31.4 feet.
- Black Oak, 6-inch diameter bears S35¼°W, 48.0 feet.
- Incense Cedar, 9-inch diameter bears N53°W, 29.9 feet.
- A found 5/8-inch re-steel rod (set inside 3/4 inches iron pipe) with attached aluminum cap marked as reported on Survey No. 5552, file date 1974 bears S1¾°W, 8.0 feet.
- A stone comparable in size (12 x 8 x 8-inch) with that recorded by P. Applegate in 1893, marked with 4 and 1 notches on adjacent sides found (disturbed) alongside said re-steel rod.
- The beginning of tangent of South bearing fence (curves West) bears South, 38 feet.

August 18, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

NOTE TO FIRST RE-ESTABLISHMENT ON NEXT PAGE

NOTE FOLLOWING FIRST RE-ESTABLISHMENT
GCDB 300200

Found 1-inch diameter galvanized iron pipe bent and brass cap missing. Replaced pipe with a 1 x 30-inch diameter flanged galvanized iron pipe with attached 2½-inch diameter brass cap marked:

Jackson County Surveyor
T39S R4E
29 | 28
—+—
32 | 33
1996

Set 26 inches deep and mound of stone around corner.

December 5, 1996
T. Newcomb
C. Charlton
P-66