

FIRST RE-ESTABLISHMENT

GCDB 300240

Quarter corner common to Sections 28 and 29, Township 39 South, Range 4 East, W.M. $V = 18^\circ$

In a found mound of stone, I set a $\frac{3}{4} \times 7\frac{1}{2}$ -inch re-steel rod, in a hole drilled 3 inches deep in bedrock, with a $2\frac{1}{2}$ -inch bronze disc marked:

Jackson County 1975
T39S R4E
 $\frac{1}{4}$ S
29 | 28

The original $21 \times 12 \times 6$ -inch stone (record, $18 \times 8 \times 6$ ins.) marked " $\frac{1}{4}$ ", found amongst mounded stones and deposited alongside as a memorial.

Original BTs recorded by P. Applegate in 1893, found as follows:

- Juniper, 12-inch diameter, scribed " $\frac{1}{4}$ S" and "BT" in exposed faces bears Record: $N63^\circ E$, 46.20 feet to scribed lower face.
- Juniper, 24-inch diameter, scribed " $\frac{1}{4}$ S" and "BT" in exposed faces bears Record: $N60^\circ W$, 58.74 feet to scribed lower face.
- Both original BTs have "W" nails in base.
- A lead plugged drill hole, in the center of a chiseled cross in a $2\frac{1}{2} \times 4 \times 1\frac{1}{2}$ feet high rock bears $N12\frac{1}{2}^\circ W$, 18.08 feet.

Corner lies about 40 feet North of the top edge of large rock mass and approximately 300 feet North of location marker on 24-inch diameter Pine, alongside road.

August 12, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor