

FIRST RE-ESTABLISHMENT

GCDB 300300

Section corner common to Sections 20, 21, 28 and 29, Township 39 South, Range 4 East, W.M.
V = 19°

In a found mound of stone, I set a 1 x 36-inch Galvanized iron pipe 30 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975	
T39S	R4E
20	21
— —	
29	28

Found (disturbed) among said stones, the original stone, marked as described by P. Applegate in 1893 and the 5/8 x 30-inch re-steel rod (lying on the ground) with attached aluminum cap marked as recorded on Survey 4754, dated 1970.

I deposited the above alongside corner.

Original BTs found as follows:

- White Fir, 19-inch diameter, with healed blazes bears record, N52°E, 47.52 feet to estimated face.
- Sawed Pine stump, 60-inch diameter bears record, S29°E, 59.40 feet to est. face.
- White Fir, 44-inch diameter, containing scribed "9" in partially exposed upper face bears S55½°W, 75.9 feet, on slope, to scribed face. Record: S50½°W, 75.9 feet.
- Ponderosa Pine, 46-inch diameter, containing scribe marks including "E" and "2" in exposed upper face, bears record, N23°W, 84.48 feet, on slope, to scribed face.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- White Fir, 9-inch diameter bears N30°E, 23.83 feet.
- White Fir, 8-inch diameter bears S23°E, 11.27 feet.
- White Fir, 14-inch diameter bears S14°W, 18.84 feet.
- White Fir, 9-inch diameter bears N47°W, 24.27 feet.

September 11, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor