

FIRST RE-ESTABLISHMENT

GCDB 300340

Quarter corner common to Sections 20 and 21, Township 39 South, Range 4 East, W.M. $V = 20\frac{1}{2}^\circ$

Found, firmly set, the 14 x 12 x 8-inch stone (Record: 12 x 8 x 6 ins.) marked " $\frac{1}{4}$ " on West face as recorded by P. Applegate in 1892.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe, set 28 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
 $\frac{1}{4}$ S
20 | 21

Original BTs recorded by P. Applegate in 1892, found as follows:

- Douglas Fir snag, 48-inch diameter, with healed blazes bears record, East, 1.98 feet to estimated face of lower blaze.
- The burned stump of a down Fir scribed " $\frac{1}{4}$ " in burned face bears Record: $S78^\circ W$, 9.90 feet to estimated lower face.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 9-inch diameter bears $S5\frac{1}{4}^\circ E$, 25.77 feet.
- Ponderosa Pine, 8-inch diameter bears $S26\frac{1}{2}^\circ W$, 42.33 feet.

Corner lies $N22\frac{1}{2}^\circ W$, about 900 feet from end of road, on blazed North-South line.

September 9, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor