

**FIRST RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 33 ONLY  
GCDB 340100**

South ¼ corner Section of Section 33, Township 39 South, Range 4 East, W.M.

Found original BT to Northeast. BT to Southwest down.

Set 1" x 36" galvanized pipe for corner from which

- The original BT a 16" yellow Pine bears N35°E, 38.3 feet.
- Scribed an 8" Pine CS-BT which bears S0°45'W, 95.8 feet.

November 9, 1929  
Boyden,  
Deputy County Surveyor

O. H. Tice, Chainman  
C. Bourne, Chainman

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

**SECOND RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 33 ONLY  
GCDB 340100**

South Quarter corner to Sections 33, Township 39 South, Range 4 East, W.M.  $V = 19^\circ$

Found, the 1-inch diameter Galvanized iron pipe, projecting 1 inch at the corner of North and West bearing fence lines, set by C. Z. Boyden on First Re-establishment in 1929.

- A Yellow Pine, recorded by Boyden, now 20-inch diameter, scribed "CS" in exposed upper face bears  $S0\frac{3}{4}^\circ W$ , 96.6 feet to center of tree at healed lower blaze. Record:  $S0\frac{3}{4}^\circ W$ , 95.8 feet.
- The original NE BT recorded by E.T.T. Fisher in 1858, now a burned Pine stump, with evidence of old axe work bears Record:  $N35^\circ E$ , 38.28 feet.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 11-inch diameter bears  $N79^\circ E$ , 40.45 feet.
- Ponderosa Pine, 21-inch diameter bears  $S11^\circ E$ , 64.17 feet.

July 9, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

**SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT**

**THIRD RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 33 ONLY  
GCDB 340100**

Quarter corner on the South line of Section 33, Township 39 South, Range 4 East, W.M.

Found the 1-inch diameter galvanized iron pipe set on the First Re-establishment, dated 1929 protruding 1 inch aboveground.

Set a 2½-inch diameter brass cap marked:

T39S R4E  
33  
¼S —  
T40S  
CS  
1989

In cement in the top of found pipe.

Bearing trees marked on the Second Re-establishment, dated 1975 found and measured to the center of lower blaze:

- Ponderosa Pine, 14-inch diameter with healed blazes and now a fence corner bears Record: N70°E. 40.65 feet. Record distance; 40.45 feet.
- Ponderosa Pine, 24-inch diameter with healed blazes bears Record: S11°E, 64.7 feet. distance: 64.17 feet.

Corner lies at the intersection of East-West and North bearing broken down fence lines and approximately 100 feet North of a dirt road course N49°E. Jenny Creek bears South approximately 200 feet.

September 25, 1989  
S. Beecher, Tech.  
T. Newcomb, Tech.

Verlyn Thomas  
County Surveyor

V = 16°  
P. -198