

## FIRST RE-ESTABLISHMENT

GCDB 340400

Quarter corner common to Sections 16 and 21, Township 39 South, Range 4 East, W.M.  $V = 20\frac{1}{2}^\circ$

Found,  $\frac{5}{8}$ -inch diameter re-steel rod, projecting 10 inches in mound of stone, with aluminum cap marked as noted on Survey No. 5552, file date 1974, with original stone (14 x 14 x 7-inch marked " $\frac{1}{4}$ ") alongside.

Over said rod, I drove a 1 x 36-inch Galvanized iron pipe 26 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975

$\frac{1}{4}$ S

16

—  
21

And deposited found aluminum cap and original stone alongside.

Original BTs recorded by P. Applegate in 1893, found as follows:

- Cedar, 49-inch diameter, containing scribed " $\frac{1}{4}$ " in partially exposed face bears  $S40^\circ E$ , 29.4 feet to center of tree. Record:  $S40^\circ E$ , 29.04 feet.
- White Fir, 33-inch diameter, with healed blaze bears  $N17^\circ W$ , 16.30 feet to center of tree. Record:  $N17^\circ W$ , 15.84 feet.

I marked a new tree CS BT:

- White Fir, 12-inch diameter bears  $N75^\circ W$ , 24.62 feet to center of tree at lower blaze.

Corner lies about 1,100 feet West of the end of road.

Sept 9, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor