

## FIRST RE-ESTABLISHMENT

GCDB 400200

Section corner common to Sections 27, 28, 33 and 34, Township 39 South, Range 4 East, W.M.  
V = 18°

Found, in mound of stone, a  $\frac{5}{8}$  x 30-inch re-steel rod, with attached aluminum cap, as reported on Survey No. 5552, file date 1974.

I replaced the above and deposited it alongside a 1 x 36-inch Galvanized iron pipe set 28 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975	
T39S	R4E
28	27
33	34

Original BTs recorded by S. Truax in 1859, found as follows:

- Black Oak, 23-inch diameter, with healed blazes bears Record: N22°E, 66.66 feet to estimated face of lower blaze. Re-measured 67.48 feet to center of tree.
- Sugar Pine, 12-inch diameter, containing scribe marks including "T39S" bears S61°E, 38.18 feet to scribed upper face. Record: S61°E, 36.96 feet.
- Ponderosa Pine snag, 39-inch diameter bears Record: S51°W, 27.06 feet, on slope, to exposed and burned upper face.
- Ponderosa Pine, 25-inch diameter, scribed "4E S28" in partially exposed upper face bears Record: N28°W, 25.74 feet to scribed upper face.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- Black Oak, 7-inch diameter bears S21½°E, 59.09 feet.
- Black Oak, 13-inch diameter, with "W" nail in base bears S20½°W, 29.21 feet.

Corner lies about 130 feet East of ridge top.

August 14, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor