

FIRST RE-ESTABLISHMENT

GCDB 400300

Section corner common to Sections 21, 22, 27 and 28, Township 39 South, Range 4 East, W.M. V = 18°

From the following evidence at the location described below:

I set a 1 x 36-inch Galvanized iron pipe 27 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975	
T39S R4E	
21	22

28	27

Original BTs recorded by S. Truax in 1859, found as follows:

- Pine, 42-inch diameter, containing scribe marks, including "9" in exposed upper face bears Record: N38°E, 33.00 feet to scribed face.
- Sawed Pine stump, 42-inch diameter, with burned faces bears Record: S63°E, 71.28 feet to lower face.
- Sawed Pine stump, 36-inch diameter, with healed lower blaze bears Record: S12°W, 42.24 feet to estimated lower face. (The felled tree alongside contains scribed marks including "S" and "3").
- The core of a rotted and burned Pine found at record location of NW BT.

A fd. 5/8-inch diameter re-steel rod, projecting 11 inches in a mound of stone with aluminum cap mkd:

Weyerhaeuser	
T39S R4E	
21	22

28	27
1972	
O.R.L.S. 686	

Bears N34°W, 5.74 feet.

An unrecorded 16 x 14 x 14-inch stone marked "¼" found alongside, among mounded stones.

Reference, Survey No. 5552, file date 1974.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- Cedar, 7-inch diameter bears N58°E, 15.87 feet.
- Douglas Fir, 9-inch diameter bears S14°E, 49.20 feet.
- Douglas Fir, 7-inch diameter bears S14½°W, 33.90 feet.
- Cedar, 8-inch diameter bears N34°W, 27.37 feet.

Corner lies about 100 feet West of stream at road crossing and N72°W, about 71 feet from location marker on 8-inch diameter White Fir, alongside road.

August 12, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor