

FIRST RE-ESTABLISHMENT

GCDB 400600

Section corner common to Sections 3, 4, 9 and 10, Township 39 South, Range 4 East, W.M.
 $V = 19^\circ$

Found, firmly set, the 12 x 10 x 8 inches stone, marked with 5 notches on South and 3 on the East sides, as recorded by P. Applegate in 1893.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe set 24 inches in the ground with 2½-inch bronze disc marked:

Jackson County 1975	
T39S	R4E
4	3

9	10

Original BTs found as follows:

- A Pine, 33-inch diameter, containing scribe marks in exposed face bears record, $S51^\circ W$, 11.88 feet to scribed face.
- A sawed Pine stump, 57-inch diameter, containing scribe marks in exposed face bears $N13^\circ W$, 116.44 feet to scribed face. Record: $N13^\circ W$, 114.84 feet.
- A Pine, 46-inch diameter, containing scribe marks in exposed face bears $S37\frac{3}{4}^\circ E$, 91.70 feet to scribed face. Record: $S37\frac{3}{4}^\circ E$, 89.10 feet.
- A burned out Cedar, 34-inch diameter, found at record location of original NE BT.

I mounded stones around corner, deposited original stone alongside as a memorial, marked the following trees CS BT and took measurements to center of trees at lower blaze:

- White Fir, 9-inch diameter bears $N55^\circ E$, 17.2 feet.
- Sugar Pine, 15-inch diameter bears $S41\frac{1}{2}^\circ E$, 31.2 feet.
- White Fir, 9-inch diameter bears $S35\frac{1}{2}^\circ W$, 37.5 feet.
- Douglas Fir, 15-inch diameter bears $N75\frac{1}{2}^\circ W$, 28.0 feet.

September 3, 1975
Ed Graham
B. Malotte

Approved by: Edward McGinty
County Surveyor