

FIRST RE-ESTABLISHMENT

GCDB 400640

Quarter corner common to Sections 3 and 4, Township 39 South, Range 4 East, W.M. $V = 18\frac{1}{2}^\circ$

Found, firmly set, the 30 x 18 x 10-inch stone (record, 24 x 8 x 6-inch) marked " $\frac{1}{4}$ " on West face, as recorded by P. Applegate in 1893.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe set 18 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
 $\frac{1}{4}$ S
4 | 3

Original BTs found as follows:

- A White Fir stob, 29-inch diameter, scribed "BT" in exposed face bears record, N72°E, 19.80 feet to scribed face.
- A stump depression found at record location of original SW BT.

I mounded stones around corner, deposited found stone alongside as a memorial, marked the following trees CS BT and took measurements to center of trees at lower blaze:

- Sugar Pine, 7-inch diameter bears S67°E, 77.3 feet.
- Douglas Fir, 14-inch diameter bears S60°W, 37.8 feet.

Corner lies on West edge of spring branch, C. N-S, and about 360 feet West of location marker on 16-inch diameter White Fir, alongside road.

September 3, 1975
B. Malotte
Ed Graham

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 400640

Quarter corner common to Sections 3 and 4, Township 39 South, Range 4 East, W.M.

Found at the corner position exposed 12 inches and in large mound of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch brass cap marked:

Jackson County 1975
T39S R4E
¼S
4 | 3

Bearing trees recorded on First Re-establishment in 1975 found and measured to center at lower blaze: Sugar Pine, now 15-inch diameter with healed double blazes bears Record S 67° E, 77.3 feet.

- Douglas Fir, now 25-inch diameter with healed double blazes. Bears S 60° W 37.4 feet. Record: 37.8 feet.

Marked new bearing trees "CS" "BT" and measured to center at lower blaze:

- Ponderosa pine, 8-inch diameter bears N 13½° W, 26.3 feet.
- White Fir, 9-inch diameter bears N 41°¼ E, 66.0 feet.

Corner lies near western edge of drainage approximately 350 feet West of gravel road.

July 6, 2006
B. Beeman
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P - 104°
V - 15°30'