

FIRST RE-ESTABLISHMENT

GCDB 440200

Quarter corner common to Sections 27 and 34, Township 39 South, Range 4 East, W.M. $V = 20^\circ$

From the following evidence, at the location described below, I set a 1 x 36-inch Galvanized iron pipe 30 inches in the ground (leaning 18° Southerly) with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
27
¼S —
34

Original BTs recorded by S. Truax in 1859, found as follows:

- Pine, 31-inch diameter, scribed "S" in exposed upper face bears Record: $S5^\circ W$, 4.62 feet to scribed face.
- Fir stump remains found at record location of NW BT.

I mounded stones around corner, marked new trees CS BT and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 10-inch diameter bears $S38^\circ E$, 41.24 feet.
- Douglas Fir, 11-inch diameter bears $N40^\circ W$, 9.48 feet.

Corner lies on top small ridge at West end of rock outcrop, about 330 feet West of location marker on 28-inch diameter Pine, alongside road.

August 13, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 440200

Quarter corner common to Sections 27 and 34 of Township 39 South, Range 4 East, W.M.

Found at corner position exposed 8 ins. in large mound of stones, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1ST re-establishment in 1975 and marked:

T39SR4E
27
1/4S—
34
1975

Single remaining original bearing tree recorded by Sewall Truax of the GLO in 1859 found with opened upper blaze with scribe 'S' ;

- P. pine now 34 ins. diam. brs. S 7° W, 5.9 ft. to center at base; record S 5° W, 4.6 ft. to face.

Bearing trees recorded on 1st re-establishment in 1975 found with healed double blazes and measured to center at lower blaze;

- P. pine now 12 ins. diam. brs. S 38° E, 41.9 ft.; record 41.2 ft.
- D. fir now 16 ins. diam. brs. N 40° W, 11.6 ft.; record 9.5 ft.

Marked new bearing tree "CS" "BT" and measured to center at lower blaze:

D. fir 11 ins. diam. brs. N 24¼° E, 36.0 ft.

Corner lies approx. 400 ft west of cinder road.

June 29, 2009

B. Beeman

H. Durkee

Kerry K. Bradshaw

Jackson County Surveyor

P. – 140

V. – 13°30'