

FIRST RE-ESTABLISHMENT

GCDB 440600

Quarter corner common to Sections 3 and 10, Township 39 South, Range 4 East, W.M. $V = 18\frac{1}{2}^\circ$

From the following evidence at the location described below, I set a 1 x 36-inch Galvanized iron pipe 24 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
3
¼S —
10

Original BTs recorded by P. Applegate in 1893, found as follows:

- The base of a down White Fir, about 20-inch diameter, containing reverse impression of scribed "¼S" bears Record: S21°E, 53.46 feet.
- A Sugar Pine stump, 60-inch diameter, scribed "¼S" and "BT" in exposed faces bears Record: N7°W, 54.12 feet to scribed lower face.

I mounded stones around corner, marked new trees CS BT and took measurements to center of trees at lower blaze:

- White Fir, 15-inch diameter bears S1½°W, 43.35 feet.
- White Fir, 9-inch diameter bears N73½°W, 65.58 feet.

Corner lies 10 feet North of center of road, C. E-W and about 130 feet Northwest of (3) road junction.

September 2, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 440600

Quarter corner common to Sections 3 and 10, Township 39 South, Range 4 East, W.M.

Corner monument, set on First Re-establishment in 1975, now missing.

Found at corner position, exposed 12 inches and in a mound of stones, a 2-inch diameter galvanized iron pipe with 2½-inch diameter brass cap marked:

T39S R4E
S 3
¼S —
S 10
1981
ORLS 1139

Bearing trees recorded on First Re-establishment found and measured to center of tree at lower blaze, unless otherwise noted:

- Single remaining original bearing tree marked by P. Applegate in 1893.
- A sawed Sugar Pine stump 60-inch diameter bears Record: N 7° W, 54.12 feet to estimated lower face (pitched face containing illegible scribe marks now broken off).

Trees marked on First Re-establishment in 1975:

- White Fir now 15-inch diameter, high-stumped with exposed faces bears S 1½° W, 44.35 feet. Record: 43.35 feet.
- White Fir now 15-inch diameter, with healed blazes bears N 73½° W, 65.70 feet. Record: 65.58 feet.

Marked new tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Ponderosa Pine 16-inch diameter bears N 89° E, 64.53 feet.
- No other trees within limits.

Corner lies approximately 15 feet north of center of road and approximately 130 feet northwesterly of (3) road junction.

April 10, 2002
H. Durkee
T. Newcomb

Roger Roberts
Jackson County Surveyor

P. - 73
v. - 15½°