

FIRST RE-ESTABLISHMENT

GCDB 500500

The Southwest corner of Section 11, common with the Northwest corner of Section 14 (only), Township 39 South, Range 4 East, W.M.

Found projecting 3 inches in mound of stones, the 2½-inch diameter brass cap, set on BLM (1966-67) dependent re-survey. The brass cap is marked:

T39S R4E
S15 | S11
| S14
1966

The 16 x 12 x 8-inch (Peter Applegate, 1893) stone, marked with 4 and 2 grooves, is found alongside.

Remains of (S. Truax, 1859) original bearing trees were found, but their original position could not be determined.

BLM bearing trees, found with healed blaze(s) are Re-measured to center of tree(s) near base:

- White fir, 13-inch diameter bears N87°30'E, (basis of bearing) 48.76 feet. Record: 48.18 feet.
- Sawed Pine stob, 20-inch diameter bears S55°13'05"E, 26.37 feet. Record: S56°E, 27.06 feet.
- A local reference tree: (Ponderosa Pine) 15-inch diameter with partially exposed single blaze bears N60°20'19"W, 18.58 feet.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White fir, 6-inch diameter bears N60°36'50"E, 8.80 feet.
- Douglas fir, 9-inch diameter bears S26°24'40"E, 29.27 feet.

The closing corner of Sections 10 and 15, monumented on Survey No. 7637, with a 2½ diameter pipe, now projecting 6 inches from a ring of stones, with brass cap marked:

T39S R4E
S10 |
— S15 |
1978
ORLS 1139

Bears N01°57'05"E, 52.82 feet. Record(s); BLM, 56.10 feet - Survey No. 7637, 52.88 feet.

FIRST RE-ESTABLISHMENT CONTINUED NEXT PAGE

FIRST RE-ESTABLISHMENT (Continued)

GCDB 500500

The original 12 x 8 x 8-inch stone is Found, marked with 4 & 2 grooves, on the north side of the closing corner monument, as described on 1978 Weyerhaeuser report.

See Jackson County Project File No. 96-18.

From the found position of the C.C. brass cap, measurements to recovered (Applegate) bearing trees follow:

- Pine stump, 22-inch diameter, scribed "T39S R4E S10" bears N73°09'02"E, 59.58 feet to upper face. Record (1893); N73¼°E, 60.06 feet.
- Pine stump, 22-inch diameter, scribed "4E S15" bears S38°49'09"W, 57.11 feet to upper face. Record (1893); S36¾°W, 57.42 feet.
- A local reference tree, Fir stump, 16-inch diameter bears N8°04'00"W, 48.63 feet to center.

To perpetuate this location, marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir, 6-inch diameter bears S22°29'45"W, 22.76 feet.
- Ponderosa Pine, 9-inch diameter bears N68°09'38"W, 18.12 feet.

See Jackson County Project File No. 96-18 for additional information on this closing corner.

July 16, 1996
R. Frost, Tech.
T. Newcomb

Roger Roberts
County Surveyor

P.- 29A