

**FIRST RE-ESTABLISHMENT
EAST QUARTER CORNER TO SECTION 10 ONLY
GCDB 500540**

East Quarter corner to Section 10 only, Township 39 South, Range 4 East, W.M. $V = 17^\circ$

Found, firmly set, the 8 x 8 x 12-inch stone marked "¼" on West face, as recorded by P. Applegate in 1893.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe set 18 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
10 | ¼S

Original BTs found as follows:

- A sawed Fir stump, 34-inch diameter, with healed lower blaze bears record, $S34^\circ S$, 9.90 feet to estimated face.
- A Yellow Pine stump, 34-inch diameter, scribed "BT" bears Record: $N16^\circ W$, 120.12 feet to scribed face.

I mounded stones around corner, deposited original stone alongside as a memorial, marked new trees CS BT, and took measurements to center of trees at lower blaze:

- Douglas Fir, 8-inch diameter bears $S80^\circ E$, 16.91 feet.
- Douglas Fir, 8-inch diameter bears $N28^\circ W$, 2.90 feet.
- The West ¼ corner of Sections 11 bears South, 56.1 feet.

Corner lies about 650 feet North of location on 8-inch diameter Ponderosa Pine, near point of ridge, alongside road.

September 2, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND REESTABLISHMENT

**SECOND RE-ESTABLISHMENT
EAST QUARTER CORNER TO SECTION 10 ONLY
GCDB 500540**

East Quarter corner common to Section 10 only, Township 39 South, Range 4 East, W.M.

Found at the corner position, exposed 17 inches in a mound of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap set on 1st Re-establishment in 1975, marked:

JACKSON COUNTY 1975
10 | ¼S

Original bearing trees recorded by Peter Applegate of the GLO in 1893, found and measured to center at base:

- Rotted Fir remains bears S 34° E, 10.7 feet record; 9.9 feet to face.
- Pitch Pine sawed stump bears N 16° W, 121.0 feet record; 120.1 feet to face.

Bearing trees recorded on said 1st Re-establishment, found high-stumped with healed double blazes and measured to center at lower blaze:

- Douglas Fir bears S 81° E, 16.9 feet record; S 80° E.
- Douglas Fir bears N 33° W, 2.9 feet record; N 28° W.

Mark new bearing trees "CS" "BT" and take measurements to center trees at lower blaze:

- Douglas Fir, 7-inch diameter bears S 78° W, 6.3 feet.
- Sugar Pine, 6-inch diameter bears N 38½° E, 8.9 feet.

Corner lies approximately 500 feet east of a cinder road.

November 4, 2010
H. Durkee

Kerry Bradshaw
Jackson County Surveyor

P. – 219
V. – 16°10'