

FIRST RE-ESTABLISHMENT

GCDB 500600

Section corner common to Sections 2, 3, 10 and 11, Township 39 South, Range 4 East, W.M.
 $V = 17\frac{1}{2}^\circ$

Found, tipped over, the original 14 x 12 x 6-inch (Record: 12 x 8 x 8-inch) stone, marked as noted by P. Applegate in 1893, with 2 and 5 grooves on adjacent faces.

At the original position of said stone, I set a 1 x 36-inch Galvanized iron pipe 26 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975	
T39S	R4E
3	2
<hr/>	
10	11

Original BTs found as follows:

- A Cedar, 20-inch diameter, containing scribe "E" and "2" bears N12°E, 21.78 feet to scribed face. Record, N15°E, 21.78 feet.
- A sawed White Fir stump, 31-inch diameter bears Record: S33°E, 10.56 feet to partially exposed lower face.
- Sugar Pine, 20-inch diameter, with healed blazes bears record, S33°W, 4.62 feet to estimated lower face. Re-measured 5.2 feet to center of tree.
- A stump hole found at record location of original NW BT.

I mounded stones around corner, deposited original stone alongside as a memorial, marked the following trees CS BT, and took measurements to center of trees at lower blaze:

- White Fir, 11-inch diameter bears S68°E, 24.8 feet.
- Cedar, 20-inch diameter bears N52½°W, 33.1 feet.

September 3, 1975
Ed Graham
B. Malotte

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500600

Section corner common to Sections 2, 3, 10 and 11 Township 39 South, range 4 East, W.M.

Found, exposed 6 inches and in a mound of stones, the 1-inch diameter galvanized iron pipe with 2½-inch diameter brass cap set on First Re-establishment in 1975 marked:

JACKSON COUNTY 1975

T39	R4E
3	2
<hr/>	
10	11

Bearing trees recorded on First Re-Establishment in 1975 found and measured to center of tree at lower blaze:

Original trees recorded by P. Applegate in 1893:

- A cedar now 20-inch diameter with healed blazes bears N 13° E, 22.30 feet. Record: N 15° E, 21.78 feet to face of lower blaze.
- A Sugar Pine now 22-inch diameter dead and down with healed blazes bears S 33° W, 5.2 feet. Record: 4.62 feet to face of lower blaze.
- A sawed fir stump 31-inch diameter bears S 33° E, 10.90 feet. Record: 10.56 feet to partially exposed lower face.

Trees recorded on First Re-establishment in 1975:

- A cedar tree 20-inch diameter with healed blazes bears N 52½° W, 32.80 feet. Record: 33.1 feet.
- A fir stump hole with pitched face containing scribe marks "BT" bears record, S 68° E, 24.8 feet to center of hole.

Marked new trees "CS" "BT" and took measurements to center of tree at lower blaze:

- A cedar 6-inch diameter bears S 59° E, 44.20 feet.
- A White Fir 8-inch diameter bears S 24½° W, 16.90 feet.

April 10, 2002

H. Durkee
T. Newcomb

Roger Roberts
Jackson County Surveyor

P. - 74
V. - 14°