

## FIRST RE-ESTABLISHMENT

GCDB 500640

Quarter corner common to Sections 2 and 3, Township 39 South, Range 4 East, W.M.  $V = 20^\circ$

Found, firmly set, the 12 x 8 x 6-inch stone, marked "¼" on West side as recorded by P. Applegate in 1893.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe set 35 inches in the ground, with a 2½-inch bronze disc marked:

Jackson County 1975  
T39S R4E  
¼S  
3 | 2

Original BTs found as follows:

- White Fir snag, 18-inch diameter, scribed "¼S" in opened face bears Record: S19½°E, 37.62 feet to scribed face.
- The remains of a down Fir, about 14-inch diameter, found at record location of original SW BT.

I mounded stones around corner, deposited original stone alongside as a memorial, marked new trees CS BT, and took measurements to center of trees at lower blaze:

- Douglas Fir, 11-inch diameter bears S46½°E, 34.8 feet.
- Sugar Pine, 7-inch diameter bears N86½°W, 27.2 feet.

Corner lies about 1,050 feet North of location marker on Fir snag alongside road.

September 3, 1975  
Ed Graham  
B. Malotte

Approved by: Edward McGinty  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 500640

Quarter corner common to Sections 2 and 3, Township 39 South, Range 4 East, W. M.

Found at the corner position, flush in a mound of stones with the original stone alongside, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1<sup>st</sup> Re-establishment in 1975, marked:

JACKSON COUNTY 1975

T39S R4E

¼S

3 • 2

Single remaining original bearing tree recorded by Peter Applegate of the GLO in 1893, a pile of rotted fir remains, brs. record; S 19½° E, 37.6 ft. to center.

Bearing trees recorded on said 1<sup>st</sup> Re-establishment, found with healed double blazes and measured to center at lower blaze:

- D. fir now 18 ins. diam. brs. record; S 46½° E, 34.8 ft.
- S. pine now 9 ins. diam. brs. record; N 86½° W, 27.2 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- W. fir 6 ins. diam. brs. S 40¼° W, 10.8 ft.
- W. fir 7 ins. diam. brs. East, 24.8 ft.

Corner lies approx. 450 ft. east of gravel road.

April 12, 2010

H. Durkee

B. Beeman

Kerry K. Bradshaw

Jackson County Surveyor

P. – 114

V. – 17°