

**FIRST RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 2 AND 3 ONLY
GCDB 500700**

Closing corner to Sections 2 and 3 (on Township line) of Township 38 South and Township 39 South, Range 4 East.

Found 5x9x14-inch high stone, marked with cross on top, recorded by P. Applegate in 1893.

Replaced said stone with and deposited it alongside a 1x36-inch Galvanized iron pipe, with brass cap marked:

T38S
—
3 | 2
T39S R4E
C.S.
1996

Brass cap projects 3 inches in ring of stone.

Original bearing trees found as follows:

- Sugar Pine (sawed) stump, 60-inch diameter, containing partial scribed "BT" bears S82°W, (basis of bearing), 42.2 feet to scribed lower face.
- Fir stump, 36-inch diameter, axed into and rotted bears N1°E, 23.1 feet to estimated lower face.

Marked new trees "CS BT" and took measurements to center of trees at lower blaze:

- Sugar Pine, 9-inch diameter bears S65°E, 26.6 feet.
- White Fir, 24-inch diameter bears S38°W, 44.4 feet.

The corner of Sections 34 and 35 on the township line bears Westerly 52.48 feet.

Subject closing corner lies about 280 feet East of road at creek crossing.

See also Survey No. 3600, dated 1967.

May 30, 1996
R. Frost, Tech.
T. Newcomb, Tech.

Roger Roberts
County Surveyor

V = 20°

P. -24

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 2 AND 3 ONLY
GCDB 500700**

Closing corner to Section 2 and 3 only, Township 39 South, Range 4 East, W.M.

Monument set on First Re-establishment in 1996, a 1x36-inch Galvanized iron pipe with a 2½-inch diameter brass cap, marked:

T38S
—
3 | 2
T39S R4E
C.S.
1996

Was removed from ground in the root-wad of a blown-down fir tree.

From the following information, reset said monument in exact corner location, exposed 6 inches in mound of earth and stone.

Original bearing trees recorded by P. Applegate of the GLO in 1893, found and re-measured:

- Sugar Pine sawed stump, 60-inch diameter with partial "BT" in weathered lower blaze bears Record: S 82° W, 42.2 feet to face of lower blaze.
- Sawed, rotted fir stump 36-inch diameter bears Record: N 1° E, 23.1 feet to estimated face.

Bearing trees recorded on First Re-establishment in 1996, found with healed double blazes and measured to center of trees at lower blaze:

- Sugar Pine, now 12-inch diameter bears Record: S 65° E, 26.6 feet
- White Fir, now 26-inch diameter bears Record: S 38° W, 44.4 feet.

The corner monument to Sections 34 and 35, on the Township line bears westerly 52.48 feet.

Subject closing corner lies approximately 280 feet east of dirt road at seasonal creek crossing.

See Survey No. 3600 dated 1967.

October 11, 2006

H. Durkee
B. Beeman

Roger R. Roberts
Jackson County Surveyor

P. - 179
V. - 17°50'