

**FIRST RE-ESTABLISHMENT
QUARTER CORNER TO SECTION 35 ONLY
GCDB 540100**

Standard $\frac{1}{4}$ corner of Section 35, Township 39 South, Range 4 East, W.M. $V = 19\frac{1}{2}^\circ$

From the following evidence at the location described below, I set a 1 x 36-inch Galvanized iron pipe 30 inches in the ground with a 2 $\frac{1}{2}$ -inch bronze disc marked:

Jackson County 1974
T39S R4E
 $\frac{1}{4}$ S 35
—
S.C.
T40S

- An original BT., marked by E.T.T. Fisher in 1858, a Cedar now 31-inch diameter, scribed " $\frac{1}{4}$ S" in exposed upper face bears record, S20°E, 50.82 feet to scribed face.
- The original NW BT is now gone.

I mounded stone around corner, marked the following trees CS BT, and took measurements to center of trees at lower blaze:

- A Douglas Fir, 9-inch diameter bears N37°E, 34.83 feet.
- A Douglas Fir, 10-inch diameter bears S10°W, 37.60 feet.

Corner lies about 150 feet South of location marker on fence post on North side of Hwy 66.

December 5, 1974
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT
GCDB 540100
QUARTER CORNER TO SECITON 35 ONLY

Standard quarter corner common to Section 35 only, Township 39 South, Range 4 East, W.M.

Found at the corner position, exposed 6 inches and in a mound of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap set on First Re-establishment in 1974, marked:

JACKSON COUNTY 1974
T39S R4E
¼S | 35
—
S.C.
T40S

Single remaining original bearing tree recorded by E. T. T. Fisher in 1858,

- A cedar snag with exposed upper face revealing scribe marks "¼" bears Record: S20 E, 50.8 feet to face. Re-measured 51.8 feet to center at base.

Bearing trees recorded on said First Re-establishment in 1975, found with healed double blazes and measured to center of trees at lower blaze:

- Douglas Fir, now 16-inch diameter bears Record: N37°E, 34.8 feet.
- Douglas Fir sawed stump bears Record: S10°W, 37.6 feet to center of stump. Set at base of said stump a 5/8 x 24-inch rebar with a 1½-inch diameter bronze cap, exposed 3 inches marked:

JACKSON COUNTY

SURVEYOR

Bears S10°W, 36.0 feet.

Marked new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Douglas Fir 10-inch diameter bears N 40° W, 28.7 feet.

Corner lies approximately 150 feet south of Highway 66.

August 9, 2006
H. Durkee
B. Beeman

Roger R. Roberts

P. - 133
V. - 16°40'