

FIRST RE-ESTABLISHMENT

GCDB 540600

Quarter corner common to Sections 2 and 11, Township 39 South, Range 4 East, W.M. $V = 19^\circ$

Found, firmly set, the 12 x 8 x 8-inch stone marked "¼" on North face as recorded by P. Applegate in 1893.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe set 26 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
2
¼S —
11

Original BTs recorded by Applegate found as follows:

- A sawed Sugar Pine stump, 36-inch diameter, scribed "S" and "BT" in exposed faces bears Record: $N25^\circ E$, 28.38 feet to scribed lower face.
- A sawed Sugar Pine stump, 30-inch diameter, scribed "4S" and "BT" in exposed faces bears Record: $S41^\circ W$, 30.36 feet to scribed lower face.

I mounded stones around corner, deposited original stone alongside as a memorial, marked new trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 6-inch diameter bears $N24^\circ E$, 35.77 feet.
- Cedar, 12-inch diameter bears $S67^\circ W$, 36.55 feet.

Corner lies about 575 feet East of stream, C. SE.

August 28, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 540600

Quarter corner common to sections 2 and 11 of Township 39 south, Range 4 East, W.M.

Found at the corner position exposed 2 inches the 2½-inch diameter iron galvanized pipe with the 3½-inch diameter brass cap set by the BLM in 1996 (the 1975 pipe and brass cap set on First Re-establishment obviously destroyed).

Single remaining bearing tree set on First Re-establishment in 1975 found with double healed blazes and measured to center at lower blaze:

- Cedar now 21-inch diameter bears S 67° W, 36.4 feet. Record: 36.6 feet.

Marked new bearing trees with "CS" and "BT" and measured to center at lower blaze:

- Ponderosa Pine 5-inch diameter bears N 8½° W, 44.4 feet.
- Sugar Pine 28-inch diameter bears S 79° E, 128.8 feet.

Corner lies approximately 10 feet east of logging road (new since 1975).

November 1, 2006

B. Beeman
H. Durkee

Roger Roberts
Jackson County Surveyor

P - 194
V.- 16°10'