

FIRST RE-ESTABLISHMENT

GCDB 540700

Quarter corner common to Sections 35 Township 38 South and Section 2 Township 39 South, Range 4 East, W.M.

Found at corner position the 2½-inch diameter galvanized iron pipe with the 3½-inch diameter brass cap exposed 6 inches and in a mound of stones set by the BLM in 1973 and marked:

T38S 4E
S35
¼S —
S 2
T 39 S
1973

Single remaining original bearing tree recorded by Sewall Truax of the GLO in 1859

- A sugar pine sawed stump with detached partially healed lower blaze revealing scribe mark "BT" found and measured to center of stump bears S54°W, 27.8 feet. Record: 27.1 to face.

Bearing trees recorded by the BLM in 1973 found with healed single blaze and measured to center at base:

- Sugar Pine now 23-inch diameter bears Record: N7½°E, 25.7 feet.
- Fir high-stump bears Record: S11½°W, 43.9 feet.

Marked new bearing trees with "CS" and "BT" and measured to center at lower blaze:

- White Fir, 8-inch diameter bears S1¼°E, 53.6 feet.
- Douglas Fir 10-inch diameter bears N30°W, 28.9 feet.

Corner lies approximately 200 feet south of gravel road.

October 12, 2006

B. Beeman

H. Durkee

Roger R. Roberts

Jackson County Surveyor

P - 178

V - 17°15'