

**FIRST RE-ESTABLISHMENT  
CORNER COMMON TO SECTIONS 5 AND 6 ONLY  
GCDB 600100**

Standard corner common to Sections 35 and 36, Township 39 South, Range 4 East, W.M.  $V = 19^\circ$

From the following evidence, at the location described below, I set a 1 x 36-inch Galvanized iron pipe 26 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1974  
T39S R4E  
S35 | S36  
-----  
S.C.  
T40S

Original BTs recorded by E.T.T. Fisher in 1858 found as follows:

- A Cedar, 16-inch diameter, scribed "R4E T40S" in exposed upper face bears  $S88^\circ E$ , 22.95 feet to center of tree. Record:  $S88^\circ E$ , 29.04 feet.
- A Red Fir, 23-inch diameter, scribed "BT" in opened lower face bears Record:  $N62^\circ W$ , 28.38 feet to scribed face.
- Other BTs of record have been destroyed in logging operations.

I mounded stones around corner, marked the following trees CS BT and took measurements to center of trees at lower blaze:

- A Cedar, 16-inch diameter bears  $N67^\circ E$ , 25.20 feet.
- A Ponderosa Pine, 10-inch diameter bears  $S36^\circ E$ , 93.75 feet.
- A Douglas Fir, 16-inch diameter bears  $N25^\circ W$ , 24.47 feet.

Corner lies about 50 feet West of road.

December 5, 1974  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

**SECOND RE-ESTABLISHMENT  
CORNER COMMON TO SECTIONS 5 AND 6 ONLY  
GCDB 600100**

Standard corner common to Sections 35 and 36, Township 39 South, Range 4 East, W.M.

Found at the corner position, exposed 8 inches and in a mound of stones, the 1-inch diameter galvanized iron pipe with 2½-inch diameter brass cap set on First Re-establishment in 1974, marked:

JACKSON COUNTY 1974  
T39SR4E  
S35 | S36  
-----  
S.C.  
T40S

Single remaining bearing tree marked on First Re-establishment in 1974:

- A cedar snag now 18-inch diameter with partially healed blazes, exposing scribe marks "CS" and "BT" bears. record N 67° E, 25.20 feet to center of tree at lower blaze.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 12-inch diameter bears N 7¼° E, 90.8 feet.
- White Fir 8-inch diameter bears N 51¼° W, 86.5 feet.
- Cedar 5-inch diameter bears S 17° E, 32.4 feet.
- No other trees within limits.

Corner lies approximately 50 feet west of cinder road.

May 31, 2002  
H. Durkee

Roger Roberts  
Jackson County Surveyor

P.-122  
V.-15¾°