

FIRST RE-ESTABLISHMENT

GCDB 600340

Quarter corner common to Sections 23 and 24, Township 39 South, Range 4 East, W.M. $V = 22^\circ$

Found, 5/8-inch diameter re-steel rod projecting 8 inches in mound of stone, with aluminum cap marked as reported on Survey No. 6064, dated 1974.

Over said rod, I set a 1 x 36-inch Galvanized iron pipe (deposit found cap alongside) 24 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
¼S
23 | 24

Original BTS recorded by S. Truax in 1859, found as follows:

- A rotted Pine stump, about 24-inch diameter, with section alongside containing partial scribed "¼S" bears Record: S78°W, 7.26 feet to estimated face.
- A sawed Pine stump, 30-inch diameter, with burned lower face bears Record: S80°E, 3.30 feet to burned face.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 14-inch diameter bears N61½°E, 71.08 feet.
- Ponderosa Pine, 13-inch diameter bears S85½°W, 94.30 feet. (Located on East edge of road.)

Corner lies near Southeast edge of large grassy meadow.

August 21, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600340

Quarter corner common to Sections 23 and 24, Township 39 South, Range 4 East, W.M.

Found at the corner position, exposed 10 ins. in a mound of stones, the 2 ins. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on Survey No. 7704 in 1978, marked:

T39S R4E
¼
S23 S24
1978
ORLS 1139

Rotted remains of original bearing trees recorded by S. Truax of the GLO in 1859, found and measured to estimated face:

- Pine remains br. record; S 78° W, 7.3 ft.
- Pine remains br. record; S 80° E, 3.3 ft.

Bearing tree recorded on 1st Re-establishment in 1975, a down Pine high-stump with scribe marks "CS" "BT" in partially healed double blazes, brs. record; N 61½° E, 71.1 ft. to center at lower blaze.

Bearing trees of unknown origin, blazed and scribed with a chainsaw, found and measured to center at base:

- D. Fir 17 ins. diam. with healed double blazes, brs. N 4¾° W, 37.8 ft.
- Fir high-stump 14 ins. diam. with chainsaw hacks in partially healed double blazes, brs. S 77° E, 30.3 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- P. Pine 7 ins. diam. brs. N 68¼° W, 32.1 ft.
- P. Pine 5 ins. diam. brs. S 62¾° E, 19.9 ft.

Corner lies northeasterly approx. 1100 ft. from cinder road and approx. 150 ft. south of a large meadow.

October 24, 2012

H. Durkee

Scott Fein

Deputy Jackson County Surveyor

P. – 64

V. – 17°15'