

FIRST RE-ESTABLISHMENT

GCDB 600400

Section corner common to Sections 13, 14, 23 and 24, Township 39 South, Range 4 East, W.M.

Found exposed 6 inches and in a mound of stones, the 3-inch diameter galvanized iron pipe with 3½-inch diameter brass cap set by the BLM in 1966, marked:

T39S	R4E
S14	S13
S23	S24
1966	

Single remaining original bearing tree recorded by Sewall Truax in 1859, a sawed pine stump 28-inch diameter bears N 54° W, 40.65 feet to center of tree at lower blaze. Record: 40.26 feet to face of lower blaze.

Bearing trees marked by the BLM in 1966, found and measured to center of tree at base:

- White Fir, now 21-inch diameter with healed blaze bears Record: S 37° W, 77.22 feet.
- Douglas Fir, now 18-inch diameter snag with healed blaze bears Record: S 67½° E, 66.0 feet

Marked new trees "CS" "BT" and took measurements to center of tree at lower blaze:

- Ponderosa Pine 6-inch diameter bears N 33° W, 42.60 feet.
- Forked Ponderosa Pine 8-inch diameter bears S 83½° W, 43.45 feet.
- Ponderosa Pine 6-inch diameter bears S 33° E, 30.15 feet.

Corner lies on logged flat approximately 25 feet northeasterly of seasonal creek. C. - southeasterly

March 26, 2002

H. Durkee

T. Newcomb

Roger Roberts

Jackson County Surveyor

P. - 49

V. - 15°