

## FIRST RE-ESTABLISHMENT

GCDB 600500

Section corner common to Sections 11, 12, 13 and 14, Township 39 South, Range 4 East, W.M.  
V = 21°

Found, ¾ x 42-inch copper-nickel pipe, projecting 29 inches in mound of stone.

I replaced said pipe with a 1 x 36-inch Galvanized iron pipe set 30 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975	
T39S	R4E
11	12
14	13

Original BTs marked by S. Truax in 1859, found as follows:

- Sawed Pine stump, 48-inch diameter, scribed "BT" bears N37°E, 125.70 feet to scribed face. Record, N35°E, 125.40 feet.
- Sawed Pine stump, 36-inch diameter, scribed "BT" bears Record: S63°W, 48.84 feet to scribed face.
- Sawed Pine stump, 36-inch diameter, containing partial scribed "BT" bears record, N48°W, 27.06 feet to scribed face.
- Pine roots found at record location of SE BT.

I deposited found pipe alongside corner, marked the following trees CS BT, and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 11-inch diameter bears N33°E, 23.66 feet.
- Ponderosa Pine, 18-inch diameter bears S14½°E, 46.87 feet.
- Ponderosa Pine, 9-inch diameter bears S59½°W, 20.64 feet.
- Douglas Fir, 13-inch diameter bears N9°W, 17.02 feet.

Corner lies about 45 feet N45°W, of NE bearing fence line, near NW edge of meadow and about 165 feet East of location marker on 10-inch diameter Ponderosa Pine, alongside road.

August 25, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor