

## FIRST RE-ESTABLISHMENT

GCDB 600600

Section corner common to Sections 1, 2, 11 and 12, Township 39 South, Range 4 East, W.M.  
 $V = 19\frac{1}{4}^\circ$

In a found mound of stone, I set a 1 x 36-inch Galvanized iron pipe 10 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975	
T39S R4E	
2	1
-----	
11	12

Original BTs marked by S. Truax in 1859, found as follows:

- The base of a down and rotted Fir, of undetermined diameter, containing scribe marks including "T39" bears Record: N9°E, 25.74 feet.
- White Fir, 26-inch diameter, with healed blazes bears Record: S32°E, 28.38 feet to estimated lower face.
- Sugar Pine, 19-inch diameter, with healed blazes bears S10°W, 27.72 feet to estimated lower face. Record: S5°W, 27.72 feet.

Corner lies in skid road, original stone not found.

I marked the following trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 14-inch diameter bears N13¼°E, 32.07 feet.
- White Fir, 11-inch diameter bears S59°E, 23.30 feet.
- Cedar, 13-inch diameter bears N70°W, 42.17 feet.

Corner lies about 55 feet West of location marker on 6-inch diameter Douglas Fir, alongside road.

August 28, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 600600

Section corner common to Sections 1, 2, 11 and 12, Township 39 South, Range 4 East, W.M.

Found projecting 8 inches, the 1-inch diameter Galvanized iron pipe with 2½-inch diameter bronze cap marked:

Jackson County 1975  
T39S R4E  

2	1
11	12

In a ring of stone, as recorded on First Re-establishment in 1975.

Original bearing trees, marked in 1859, found as follows:

- White fir, 29-inch diameter (sawed) high stump, with face split off bears S32°15'57"E, 28.07 feet to center.
- Sugar pine, 27-inch diameter (sawed) high stump with healed blazes bears S9°23'12"W, 27.65 feet to center.

Jackson County (1975) BTs found:

- The NE Douglas Fir has been blown down and uprooted.
- White Fir, 14-inch diameter (sawed) high stump, with healed blazes bears S59°07'47"E, 21.14 feet to center.
- Cedar, 16-inch diameter with healed blaze (basis of bearing) bears N70°W, 41.82 feet to center.

Marked new trees "CS BT" and took measurements to center of trees at lower blaze:

- White fir, 6-inch diameter bears N29°41'15"E, 29.38 feet.
- Douglas fir, 14-inch diameter bears S68°23'46"E, 35.89 feet.
- Ponderosa Pine, 6-inch diameter bears S35°13'46"W, 18.35 feet.

Corner lies about 55 feet west of location marker alongside road.

June 26, 1996  
R. Frost, Tech.  
T. Newcomb, Tech.

Roger Roberts  
County Surveyor

P-29