

## FIRST RE-ESTABLISHMENT

GCDB 640300

Quarter corner common to Sections 24 and 25, Township 39 South, Range 4 East, W.M.  $V = 22^\circ$

Found,  $\frac{3}{4}$  x 42-inch copper-nickel pipe, projecting 12 inches in mound of stone.

I replaced said pipe with a 1 x 36-inch Galvanized iron pipe set 23 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975  
T39S R4E  
¼S 24  
25

Original BTs recorded by S. Truax in 1859, found as follows:

- A sawed Sugar Pine stump, 30-inch diameter, containing chaining notch (4½ inches from center of stump) in axed face bears Record: S50°W, 14.52 feet to said notch.
- A stump hole with Pine fragments found at record location of original NW BT.

I deposited found pipe alongside corner, marked new trees CS BT, and took measurements to center of trees at lower blaze:

- Douglas Fir, 8-inch diameter bears S11°W, 7.82 feet.
- Douglas Fir, 10-inch diameter bears N5°W, 46.42 feet.

Corner lies 35 feet West of ridge top and about 250 feet East of location marker on 5-inch diameter Ponderosa Pine, alongside road.

August 19, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 640300

Quarter corner common to Sections 24 and 25, Township 39 South, Range 4 East, W.M.

Found at the corner, exposed 8 inches and in a mound of stones, the 1-inch diameter galvanized iron pipe with 2½-inch diameter brass cap set on First Re-establishment in 1975, and marked:

Jackson County 1975  
T39S R4E  
24  
¼S —  
25

Original bearing tree recorded by Sewall Truax in 1859,

- A Sugar Pine, now a 30-inch diameter sawed stump bears Record: S 50° W, 14.52 feet to chaining notch.

Bearing trees marked on First Re-establishment in 1975, found and measured to center of tree at lower blaze:

- Douglas Fir, now 12-inch diameter and high-stumped with healed blazes bears Record: N 5° W, 46.42 feet.
- Douglas Fir, now a 15-inch diameter sawed stump bears S 11° W, 7.66 feet. Record: 7.82 feet.

Marked new trees "CS" "BT" and took measurements to center of tree at lower blaze:

- Douglas Fir 6-inch diameter bears N 10¼° E, 48.78 feet.
- White Fir 5-inch diameter bears S 39° E, 6.66 feet.
- No other trees within limits.

Corner lies on northwesterly corner of top of knob and approximately 350 feet east of cinder road.

March 28, 2002

H. Durkee

T. Newcomb

Roger Roberts

Jackson County Surveyor

P. - 56

V. - 18½°