

FIRST RE-ESTABLISHMENT

GCDB 640400

Quarter corner common to Sections 13 and 24, Township 39 South, Range 4 East, W.M. $V = 19\frac{3}{4}^\circ$

From the following information at the location described below, I set a 1 x 36-inch Galvanized iron pipe 24 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
13
—
24

Original BTs recorded by S. Truax in 1859, found as follows:

- A sawed Pine stump, 30-inch diameter, scribed "BT" bears Record: N54°E, 40.92 feet to scribed face.
- A Pine stump, 36-inch diameter, containing chain notch and scribed "T" in opened lower face bears Record: S74°E, 21.78 feet to scribed face.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 7-inch diameter bears N69½°E, 14.34 feet.
- Ponderosa Pine, 8-inch diameter bears S32°E, 40.20 feet.

Corner lies 200 feet East of East edge of clearing and about 300 feet East of old rail road bed.

August 21, 1975
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 640400

Quarter corner common to Sections 13 and 24 of Township 39 South, Range 4 East, W.M.

Found at corner position , exposed 18 ins., in a large mound of stones, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1st re-establishment in 1975 and marked:

Jackson County Surveyor 1975

T39SR4E

13

1/4 ———

24

Single remaining original bearing tree recorded by Sewall Truax of the GLO in 1859 found with healed blaze and measured to center at base:

- Pine rotted sawed stump brs. record N54°E, 40.9 ft.

Bearing trees recorded on said 1st re-establishment found with healed double blazes and measured to center at lower blaze;

- D. fir now 16 ins. diam. brs. N68½°E, 14.3 ft. record; N69½°E.
- P. pine now 24 ins. diam. brs. S32°E, 40.6 ft. record; 40.2 ft.

Marked new bearing trees "CS" "BT" and measured to center at lower blaze:

- W. fir 7 ins. diam. brs. N33½°W, 10.0 ft.
- P. pine 6 ins. diam. brs. S87°W, 21.8 ft.

Corner lies approx. 700 ft. west of cinder road.

October 7, 2009

B. Beeman

H. Durkee

Kerry K. Bradshaw

Jackson County Surveyor

P. – 128

V. – 16°30'