

FIRST RE-ESTABLISHMENT

GCDB 640500

Quarter corner common to Sections 12 and 13, Township 39 South, Range 4 East, W.M. $V = 20\frac{1}{2}^\circ$

From the following evidence at the location described below, I set a 1 x 36-inch Galvanized iron pipe 24 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975
T39S R4E
12
¼S —
13

Original BTs recorded by S. Truax in 1859, found as follows:

- A sawed Pine stump, 34-inch diameter, scribed "B" and partial "T" in exposed face bears Record: S22°E, 25.08 feet to scribed face.
- A dead and down Pine, 12-inch diameter, with complete set of scribing, found at record location of original NE BT.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 10-inch diameter bears N40°E, 28.30 feet.
- Douglas Fir, 8-inch diameter bears S28°W, 4.30 feet.

Corner lies about 450 feet West of location marker posted alongside road.

August 26, 1975
Ed Graham
B. Malotte

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 640500

Quarter corner common to Sections 12 and 13, Township 39 South, Range 4 East, W.M.

Found 1-inch diameter galvanized iron pipe with 2½-inch diameter brass cap set on First Re-establishment in 1975, exposed 12 inches and marked:

JACKSON COUNTY 1975
T39S R4E
12
¼S —
13

Bearing trees marked on First Re-establishment in 1975 found high-stumped with healed blazes and took measurements to center of trees at lower blaze:

- Douglas Fir now 15-inch diameter bears Record: N 40° E, 28.3 feet.
- Douglas Fir now 12-inch diameter bears Record: S 28° W, 4.3 feet.

Marked new trees "CS" "BT" and took measurements to center of tree at lower blaze:

- Douglas Fir 5-inch diameter bears S 65½° W, 51.10 feet.
- Douglas Fir 5-inch diameter bears N 5° E, 50.45 feet.
- No other trees within limits.

Corner lies on flat ground in heavily logged area.

Search coordinates: 42°11'07.4"
122°17'50.2"

March 22, 2002

H. Durkee
T. Newcomb

Roger Roberts
Jackson County Surveyor

P.-46
V.-17°