

## FIRST RE-ESTABLISHMENT

GCDB 640600

Quarter corner common to Sections 1 and 12, Township 39 South, Range 4 East, W.M.  $V = 20\frac{3}{4}^\circ$

In a found mound of stones, I set a 1 x 36-inch Galvanized iron pipe 25 inches in the ground, (pipe leans North,  $15^\circ$ ) with a 2½-inch bronze disc marked:

Jackson County 1975  
T39S R4E  
1  
¼S —  
12

Original BTs recorded by S. Truax in 1859, found as follows:

- The base of a down and rotted Pine, about 15-inch diameter, scribed "¼S" and "BT" in exposed faces bears Record: N59°W, 42.24 feet.
- A stump hole with rotted Pine remains found at record location of South BT.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 7-inch diameter bears S26¾°W, 26.65 feet.
- Douglas Fir, 7-inch diameter bears N73½°W, 28.23 feet.

Corner lies about 350 feet East of road.

August 28, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 640600

Quarter corner common to Sections 1 and 12, Township 39 south, Range 4 East, W.M.

Found at the corner, exposed 12 inches and in a mound of stones 2 feet square x 1 foot high, the 1-inch diameter galvanized iron pipe with 2½-inch diameter brass cap set on First Re-establishment in 1975, and marked:

JACKSON COUNTY 1975  
T39S R4E  
1  
¼S —  
12

Bearing trees marked on First Re-establishment in 1975 found and measured to center of sawed stumps:

- Douglas Fir, now 20-inch diameter bears Record: N 73½° W, 28.23 feet.
- Douglas Fir, now 18-inch diameter bears Record: S 26¾° W, 26.65 feet.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Douglas Fir, 6-inch diameter bears N 50½° W, 49.80 feet.
- White Fir, 8-inch diameter bears S 36° E, 11.93 feet.
- No other trees within limits.

Corner lies on gentle southerly slope in heavily logged area and approximately 300 feet east of dirt road.

March 28, 2002  
H. Durkee  
T. Newcomb

Roger Roberts  
Jackson County Surveyor

P. - 55  
V. 17½°