


**FIRST RE-ESTABLISHMENT  
CORNER COMMON TO SECTIONS 36 AND 31 ONLY  
GCDB 700100**

Standard corner common to Sections 36 and 31, Township 39 South, Ranges 4 and 5 East, W.M.  
V=17°

From the following evidence, at the location described below, I set a 1 x 36-inch Galvanized iron pipe 26 inches in the ground with a 2½-inch bronze disc marked:



Original BTs recorded by E.T.T. Fisher in 1858 found as follows:

- The core, 24-inch diameter, of a sawed Yellow Pine stump bears Record: N20°E, 9.24 feet to estimated face.
- A sawed Douglas Fir stump, 45-inch diameter bears S25°E, 38.4 feet to estimated face of blaze. Record: S25°E, 37.62 feet.
- A sawed Douglas Fir stump, 36-inch diameter, scribed "BT" in opened lower face bears record, S34°W, 9.90 feet to scribed face.
- A sawed Sugar Pine stump, 28-inch diameter, with visible scribe marks in weathered face bears Record: N40°W, 64.68 feet to scribed face.

I mounded stones around corner and marked the following trees CS BT, and took measurements to center of trees at lower blaze:

- A Cedar, 8-inch diameter bears N16°E, 32.75 feet.
- A Sugar Pine, 7-inch diameter bears S84°E, 32.15 feet.
- A White Fir, 9-inch diameter bears S46½°W, 30.73 feet.
- A Ponderosa Pine, 20-inch diameter bears N34½°W, 63.80 feet.

Corner lies about 700 feet East of road C. S70°W.

December 4, 1974  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

**SECOND RE-ESTABLISHMENT  
CORNER COMMON TO SECTIONS 36 AND 31 ONLY  
GCDB 700100**

Standard corner common to Sections 36 and 31, Township 39 South, Ranges 4 and 5 East, Willamette Meridian.

Found corner monument set on First Re-establishment in 1974 bent and dislodged from position.

From following evidence set at corner position a 1x30-inch flanged galvanized iron pipe with attached 2½-inch diameter brass cap, 24 inches in the ground, marked:

JACKSON COUNTY SURVEYOR  
T39S  
S36 | S31  
-----  
R4E S.C. R5E  
T30S  
2002

Original bearing trees recorded by E.T.T. Fisher in 1858 found:

- A sawed pine stump core 24-inch diameter bears record, N20°E, 9.24 feet to estimated face.
- A sawed fir stump 36-inch diameter bears record, S34°W, 9.90 feet to scribed "BT" on burnt lower face.
- A sawed pine stump 28-inch diameter bears record, N40°W, 64.68 feet to scribed, weathered lower face.

Bearing trees marked on First Re-establishment in 1974 found and measured to center of tree at lower blaze:

- A cedar 14-inch diameter with healed blazes bears record, N16°E, 32.75 feet.
- A Sugar Pine 7-inch diameter, dead with partially healed blazes bears record, S84°E, 32.15 feet.
- A White Fir now 14-inch diameter, high-stumped with healed blazes bears record, S46½°W, 30.73 feet.
- A sawed Ponderosa Pine stump 25-inch diameter, with partially healed lower blaze with visible scribe marks "BT" bears record, N34½°W, 63.80 feet.

Marked new trees "CS" "BT" and took measurements to center of tree at lower blaze:

- Cedar 7-inch diameter bears S42°E, 77.30 feet.
- Cedar 10-inch diameter bears S4½°E, 29.10 feet.
- White Fir 8-inch diameter bears N70½°W, 60.0 feet.
- No other trees within limits.

Corner lies approximately 700 feet southeasterly of cinder. C. - S 70° W

April 8, 2002  
H. Durkee

Roger Roberts  
Jackson County Surveyor

p. - 69  
v. - 17½°