

## FIRST RE-ESTABLISHMENT

GCDB 700600

Section corner common to Section 1 and 12, Township 39 South, Range 4 East, and Section 6 and 7, Township 39 South, Range 5 East, W.M.  $V = 19\frac{3}{4}^\circ$

From the following evidence, at the location described below I set a 1 x 36-inch Galvanized iron pipe 30 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975

T39S	
1	6
<hr/>	
12	7
R4E R5E	

Original BTs recorded by S. Truax in 1859, found as follows:

- A sawed Fir stump, 36-inch diameter, containing axed chain notch bears Record: S52°E, 25.74 feet to said notch.
- A Fir, 20-inch diameter, containing scribed "S" and "B" in opened faces bears Record: S79°W, 54.12 feet to scribed lower face.
- The stump hole of a down and rotted Pine (undetermined diameter) containing axed chain notch, found at record location of original NW BT.
- The NE BT is now gone.

Ring of painted stones bear S87°W, 13.5 feet. The  $\frac{5}{8}$  x 30-inch re-steel rod with aluminum cap marked as reported on Survey No. 5550, dated 1973, found among stones, apparently having been run over by a tractor. Blazed lines bear North, South and West from said stones.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

- White Fir, 12-inch diameter bears N59°E, 33.58 feet.
- White Fir, 14-inch diameter bears S15°E, 35.50 feet.
- Sugar Pine, 8-inch diameter bears S38¼°W, 122.96 feet.
- Sugar Pine, 5-inch diameter bears N69°W, 43.96 feet.

Corner lies about 100 feet North of old logging road.

August 27, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 700600

Section corner common to Section 1 and 12, Township 39 South, Range 4 East, and Section 6 and 7, Township 39 South, Range 5 East, W.M.

Found the 2½ ins. diam. brass cap set on the First Re-establishment, dated 1975, mkd:

Jackson County 1975

T39S	
1	6
12	7
R4E R5E	

Protruding 2 ins. above ground.

From which bearing trees marked in 1975 found;

- White Fir 21 ins. diam with healed blazes brs. record N59°E, 33.58 ft.
- White Fir snag 19 ins. diam. with healed blazes brs. S16°E, 35.50 ft. Record brg. S15°E.
- Sugar Pine 12 ins. diam. with healed blazes brs. record N69°W, 43.96 ft.
- Southwest bearing tree is now a stump.

Mark new trees "CS BT" and measure to center of tree at base;

- White Fir 10 ins. diam. brs. S32½°E, 24.85 ft.
- White Fir 13 ins. diam. brs. S75°W, 51.40 ft.

Corner is located in sparse timber with blazed and painted line to North

September 14, 2011  
S. Beecher  
S. Fein

Kerry K. Bradshaw  
County Surveyor

P.-11  
Series II Book I  
V = 15°