

FIRST RE-ESTABLISHMENT

GCDB 100440

Quarter corner common to Section 13, Township 40 South, Range 4 West and Section 18, Township 40 South, Range 3 West, W.M. $V = 21\frac{1}{2}^\circ$

Found the single remaining original BT, recorded by S. Lackland in 1882, now a White Oak stob, 4-inch diameter, 5 feet high, containing reverse impression of partial scribed "¼" and "BT" in opened faces.

From the preceding evidence I set a 1 x 36-inch Galvanized iron pipe, 28 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1977
T40S
¼S
13 | 18
R4W R3W

From which

- The above-described original BT bears record, $N72^\circ E$, 15.18 feet to scribed (reverse) face.

Original stone not found.

I mounded stones around corner, marked the following trees 'CS BT' and took measurements to center of trees at lower blaze:

- White Oak, 7-inch diameter bears $N78^\circ E$, 23.17 feet.
- Ponderosa Pine, 14-inch diameter bears $S34\frac{1}{2}^\circ W$, 7.07 feet.

Corner lies on steep (60%) South slope, about 375 feet North of location marker on 8-inch diameter Alder alongside road, C. $N65^\circ W$.

May 2, 1977
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor