

FIRST RE-ESTABLISHMENT

GCDB 100500

Section corner common to Sections 12 and 13, Township 40 South, Range 3 West and Sections 7 and 18, Township 40 South, Range 3 West, W.M.

Found firmly set an unmarked 11 x 11 x 6-inch sandstone. Record: 14 x 10 x 8-inch.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe, set 30 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1977

T40S	
12	7

13	18
R4W R3W	

Original BTs recorded by S. Lackland in 1882, found as follows:

- Douglas Fir, 21-inch diameter, with healed blaze bears Record: N9°E, 7.92 feet to estimated face. Re-measured 8.42 feet to center of tree.
- The stump hole of a down (tipped over) Douglas Fir bears Record: S35°E, 15.18 feet.
- Douglas Fir snag, 12-inch diameter, scribed "T40S R4WS" in partly opened face bears Record: S10°W, 19.14 feet to scribed face.
- NW BT now gone.

I deposited found stone alongside corner, marked the following trees CS BT, and took measurements to center of trees at lower blaze:

- Douglas Fir, 15-inch diameter bears S74°E, 67.53 feet.
- Douglas Fir, 15-inch diameter bears S44°W, 29.97 feet.
- Black Oak, 7-inch diameter bears N72½°W, 59.10 feet.

Corner lies in bottom of draw, C. N50°E, about 400 feet S50°W, of location marker on 16-inch diameter Maple in bottom of Billy's Gulch.

B. Malotte
R. Frost
May 4, 1977

Approved by: Edward McGinty
County Surveyor