

**FIRST RE-ESTABLISHMENT  
CORNER COMMON TO SECTIONS 1 AND 6 ONLY  
GCDB 100700**

Section corner common to Section 1, Township 40 South, Range 4 West and Section 6, Township 40 South, Range 3 West only, W.M.  $V = 22\frac{1}{2}^\circ$

Found firmly set, the original 11 x 9 x 6-inch. Record: 15 x 10 x 10-inch stone, projecting 3 inches and marked with notches and chiseled cross on top.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe set 30 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1977  
T39S  
-----  
1 | 6  
T40S  
R4W R3W

Original BTs recorded by S. Lackland in 1882 found as follows:

- The base of a down fir, 17-inch diameter, with healed blazes bears Record: N68°E, 14.52 feet.
- The most Northerly branch, 13-inch diameter with healed blazes, of four live oaks with common base bears S40°E, 9.20 feet to center of tree (branch) near base. Record: S45°E, 8.58 feet.
- Douglas fir, 29-inch diameter, with healed blazes bears S89°W, 14.76 feet to center of tree. Record: S89°W, 13.86 feet.
- Live Oak, 10-inch diameter, with scribe marks visible in exposed faces bears N70°W, 4.80 feet to scribed lower face. Record: N70°W, 4.62 feet.

I deposited found stone alongside corner and marked a new tree CS BT:

- The most Southerly branch, 12-inch diameter of a double live Oak bears N4½°W, 32.77 feet to center of tree at lower blaze.

Corner lies about 35 feet East of draw and near the South end of rock outcrop sloping SW and approximately 220 feet West of the (brass cap) closing corner of Section 31 and 36.

June 7, 1977  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor