

FIRST RE-ESTABLISHMENT
QUARTER CORNER TO SECTION 6 ONLY
GCDB 140700

Quarter corner to Section 6 only, Township 40 South, Range 3 West, W.M. $V = 16^\circ$

Found at the corner, projecting 12 inches, the 1-inch diameter iron pipe with brass cap marked:

S.C.
 $\frac{1}{4}S$ —
S6
1918

SEE Project File 77-22

Bearing trees marked by Mensch and Wright, found:

- Laurel, 14-inch diameter, containing scribe marks including "S" in partially exposed face bears $S49\frac{1}{2}^\circ E$, 41.36 feet to center of tree. Record: $S47^\circ E$, 40.92 feet.
- Laurel, 15-inch diameter, containing scribe marks in partially opened and rotted face bears $S59\frac{1}{2}^\circ W$, 33.74 feet. Record: $S60^\circ W$, 36.96 feet.
- I marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:
- Fir, 5-inch diameter bears $S75^\circ E$, 21.95 feet.
- Fir, 4-inch diameter bears $S4\frac{1}{2}^\circ E$, 9.00 feet.

Corner lies on North sloping ridge.

June 9, 1977

R. Frost

B. Malotte

Recorded: August 15, 1980

Approved by: Edward McGinty
County Surveyor

P. -118