

FIRST RE-ESTABLISHMENT

GCDB 300240

Quarter corner common to Sections 28 and 29, Township 40 South, Range 3 West, W.M.

At the corner found lying on the ground, the original 22 x 10 x 6-inch basalt stone, marked "¼" facing down.

Replaced found stone with and deposited it alongside a 1 x 24-inch Galvanized iron pipe, 20 inches in the ground with a 2½-inch brass cap marked:

T40S R3W
¼S
29 | 28
C.S.
1992

Original bearing trees recorded by S.W. Lackland in 1882 found and measured to estimated face:

- Black Oak, 23-inch diameter, with healed blazes bears S70½°E, 42.24 feet. Record: S71°E.
- Pine stump hole with burned Pine remains bears Record: S4°W, 78.54 feet.

Marked new trees "CS" "BT" and took measurements to the center of tree at lower blaze:

- Ponderosa Pine, 21-inch diameter bears South 16.20 feet.
- Black Oak, 13-inch diameter in a clump of Oaks bears S29¾°W, 43.78 feet.
- Mt. Mahogany, 6-inch diameter bears N49½°W, 58.85 feet.

Corner lies about 45 feet West of spur, course S45°W, large clearing west.

April 20, 1992
T. Newcomb, Tech.
H. Durkee, Tech.

Verlyn Thomas
County Surveyor

V = 18°
P.-21