

FIRST RE-ESTABLISHMENT

GCDB 300500

Section corner common to Sections 8, 9, 16 and 17, Township 40 South, Range 3 West, W.M.

At the corner, found projecting 3 inches in mound of stone, the 2-inch diameter iron pipe with 3-inch diameter standard BLM brass cap marked:

T40S	R3W
S8	S9
S17	S16
1964	

As recorded by the BLM in 1964.

Bearing trees marked by BLM found:

- Douglas Fir, 16-inch diameter with healed single blaze bears N76°E, 14.0 feet to center. Record: 13.86 feet.
- Base of a tipped over Douglas Fir, 10-inch diameter bears Record: S61°E, 24.42 feet.
- Broken off Fir snag, 10-inch diameter, containing scribe marks in partially exposed single face, bears S57°W, 3.96 feet to center.
- Douglas Fir, 21-inch diameter, with healed single blaze bears Record: N12°W, 26.40 feet to center.

Original bearing trees recorded by S. Lackland in 1882 found:

- Black Oak stob, 29-inch diameter, with down tree alongside bears N44°E, 44.17 feet to center. Record: N46°E, 40.92 feet.
- Douglas Fir snag, 22-inch diameter, with axed and burned lower face, containing scribed "B", bears S60°W, 73.2 feet to scribed face. Record: S56°W, 72.60 feet.
- Douglas Fir, 33-inch diameter, with (re)healed lower face bears N17°W, 47.20 feet to center. Record: N19°W, 44.88 feet.

To perpetuate this location marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Douglas Fir, 16-inch diameter bears S15½°E, 54.20 feet.
- Douglas Fir, 8-inch diameter bears S70°W, 48.50 feet.

Corner lies 12 feet North of stream C. N60°W, and 80 feet North of old logging road.

Also See: Jackson County Field notes page 17.

February 24, 1983

R. Frost

Witness: T. Newcomb, USFS

Edward McGinty

County Surveyor

V = 20°

P.-17