

## FIRST RE-ESTABLISHMENT

GCDB 300540

Quarter corner common to Section 8 and 9, Township 40 South, Range 3 West, W.M.  $V = 20\frac{1}{2}^\circ$

Found firmly set, the 15 x 14 x 5-inch stone (record, 15 x 14 x 8 ins) projecting 6 inches and marked "¼" on West face as noted by S. Lackland in 1882. Said stone also marked with cross on West face.

I replaced the above with a 1 x 36-inch Galvanized iron pipe, set 28 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1976  
T40S R3W  
¼S  
8 | 9

Both original BTs are now gone. A root hole found at record location of original NW BT. Black Oak, 5-inch diameter, with metal tag marked "¼ Cor. J. Austin" bears  $N76^\circ W$ , 5.20 feet to center of tree. This is 1961 USFS reference tree. Corner report on file, pg. 1, 1976 field notes.

I deposited original stone alongside corner, marked the following trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 17-inch diameter bears  $S21^\circ E$ , 23.62 feet.
- Douglas Fir, 11-inch diameter bears  $N54^\circ W$ , 25.53 feet.

Corner lies an estimated 760 feet North of blazed, 6-inch diameter White Oak on top of major East-West ridge, about 320 feet North of NW-SE draw and about 100 feet South of spur, C. E-W.

January 5, 1976  
R. Frost  
T. Newcomb, USFS

Approved by: Edward McGinty  
County Surveyor