

FIRST RE-ESTABLISHMENT

GCDB 340600

Quarter corner common to Sections 4 and 9 of Township 40 South, Range 3 West, W.M.

Found at corner position exposed 6 inches, the 2½-inch diameter galvanized iron pipe with a 3½-inch diameter brass cap set by the BLM in 1964 and marked:

T40S R3W
S4
¼S —
S9
1964

Single remaining original bearing tree recorded by Rufus S. Moore of the GLO in 1883 found dead, down and rotted bears Record: S42°W, 19.8 feet to stump hole.

Bearing trees recorded by the BLM in 1964 found with healed single blazes and measured to center at base:

- Douglas Fir now 12-inch diameter bears Record: N13°W, 21.8 feet.
- Douglas Fir now 8-inch diameter bears S80°W, 6.1 feet. Record: 5.9 feet.

Marked new bearing trees "CS" "BT" and measured to center at lower blaze:

- Madrone 10-inch diameter bears S1½°E, 6.4 feet.
- Douglas Fir 7-inch diameter bears N85½°E, 18.6 feet.

Corner lies approximately 100 feet east of spur road on 50% slope,

February 19, 2008

B. Beeman

H. Durkee

Roger R. Roberts

Jackson County Surveyor

P. - 31

V - 19°50'