

FIRST RE-ESTABLISHMENT

GCDB 340700

Quarter corner common to Section 33, Township 39 South, Range 3 West and Section 4, Township 40 South, Range 3 West, W.M. $V = 19\frac{3}{4}^\circ$

- Found a mound of stones from which an original bearing tree, now a hollow 24 inch Black Oak with healed blaze bears $N9^\circ E$, 47.2 feet to face of blaze (original Record: Black Oak, 16 inches, $N7^\circ E$, 70 lks.).
- The original bearing tree, now a 48 inch Fir with a visible scribe mark bears $S15^\circ W$, 21.5 feet. (Original Record: A Fir, 36 in., $S12^\circ W$, 40 lks.).

From which evidence I set a 1" x 36" Galvanized iron pipe 32 inches in the ground with a 2½-inch brass cap marked:

T39S R3W
Section 33
—————
Section 4
C.S. 1973
T40S R3W

From which:

- A Black Oak, 6-inch diameter bears $N32^\circ E$, 10.5 feet to center of tree, marked CS BT.
- A Douglas Fir, 8-inch diameter bears $S65^\circ E$, 11.9 feet to center of tree, marked CS BT.

February 24, 1973
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor