

## FIRST RE-ESTABLISHMENT

GCDB 400140

Quarter corner common to Sections 33 and 34, Township 40 South, Range 3 West, W.M.  
 $V = 17\frac{3}{4}^\circ$

At the corner location I set a 2 x 36-inch Galvanized iron pipe projecting 6 inches with 2½-inch diameter brass cap marked:

T34S R3W  
33 | 34  
¼S  
CS  
1980

From which I found the following original evidence recorded by S.W. Lackland in 1882:

- Dead and Down Pine, 24-inch diameter with "¼S" scribes visible the stump of which bears record N55°E, 11.22 feet to estimated face.
- Black Oak, 16-inch diameter with "¼S" scribes visible in exposed upper face bears Record: S52°W, 36.30 feet on slope, to estimated face. Re-measure 34.81 feet to center of tree at lower blaze.

I marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Douglas Fir, 7-inch diameter bears N58¾°E, 44.25 feet.
- Black Oak, 7-inch diameter bears N41¾°W, 16.40 feet.
- I drove a 7 feet angle iron with monument marker sign attached 1.5 feet East of corner.
- Location marker on 26-inch diameter Maple 1800 feet West of corner alongside road.

January 23, 1980

B. Malotte

Witness: C. Davidson, USFS

D. Thomas, USFS

Approved by: Edward McGinty

County Surveyor