

FIRST RE-ESTABLISHMENT

GCDB 400200

Section corner common to Sections 27, 28, 33 and 34, Township 40 South, Range 3 West, W.M.
 $V = 16^\circ$

Found, at the corner a 22 x 12 x 10-inch stone exposed 8 inches. Marked with 3 notches on East side, 1 notch on South side and "X" on top firmly in place as set by S. W. Lackland in 1882. I replaced said stone with a 2 x 36-inch Galvanized iron pipe projecting 6 inches with a 2½-inch diameter brass cap marked:

T40S R3W	
28	27
33	34
CS	
1980	

From which I found the following references recorded by above Surveyor:

- Dead and down Black Oak, 14-inch diameter, the stump hole of which bears Record: N15°E, 8.58 feet.
- Black Oak stump, 24-inch diameter bears S20°E, 8.6 feet to center. Record: S20°E, 7.92 feet.
- Black Oak, 21-inch diameter with healed double blazes bears S5°W, 46.68 feet to center of tree at lower blaze. Record: S5°W, 47.52 feet.
- Dead and down Black Oak, 22-inch diameter with reverse "WS28" scribes visible, the stump hole of which bears N48°W, 44.10 feet to center. Record: N48°W, 50.16 feet.

I marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Black Oak, 12-inch diameter bears N55°E, 59.0 feet.
- Douglas Fir, 13-inch diameter bears S31°E, 33.08 feet.
- Ponderosa Pine, 7-inch diameter bears N86°W, 59.39 feet
- I drove a 7 feet angle iron with monument sign attached 1 foot Northwest of corner. I then raised mound of stone and deposited original stone alongside corner.
- Location marker on a Douglas Fir, 10-inch diameter alongside Little Grey Back Trail S45°W, about 850 feet from corner.

January 23, 1980

B. Malotte

Witness: C. Davidson USFS

D. Thomas USFS

Approved by: Edward McGinty

County Surveyor