

FIRST RE-ESTABLISHMENT

GCDB 400640

Quarter corner common to Sections 3 and 4, Township 40 South, Range 3 West, W.M. $V = 20^\circ$

Found tipped over, the original 17 x 7 x 7-inch stone, (Record: 17 x 10 x 7-inch) marked: " $\frac{1}{4}$ ".

I replaced said stone, with a 1 x 36-inch Galvanized iron pipe set 27 inches in the ground, with a 2½-inch bronze disc marked:

Jackson County 1977
T40S R3W
 $\frac{1}{4}$ S
4 | 3

Original bearing trees recorded by S. Lackland in 1882 found as follows:

- White Oak, 21-inch diameter with healed blazes bears $S25^\circ E$, 3.96 feet to estimated upper face. Record: $S55^\circ E$, 3.96 feet.
- The stump hole and base of a down and rotted Black Oak, 6-inch diameter, containing reverse impressions of scribe marks including " $\frac{1}{4}$ S" bears Record: $N71^\circ W$, 9.24 feet.

I deposited original stone alongside corner, marked new trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 11-inch diameter bears $S12^\circ E$, 22.21 feet.
- Ponderosa Pine, 17-inch diameter bears $N24^\circ W$, 12.52 feet.

Corner lies on SE slope, approximately 1,000 feet North of road and 68 feet West of location marker on 15-inch diameter Fir located 13 feet East of bottom of draw, C. $S30^\circ W$.

January 11, 1977
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor