

FIRST RE-ESTABLISHMENT

GCDB 440700

Quarter corner common to Section 34, Township 39 South, and Section 3, Twp. 40 South, Range 3 West, W.M. $V = 19^\circ$

From the following evidence, at the location described below, I set a 1x36-inch Galvanized iron pipe, 21 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1977
T39S R3W
34
¼S —
3
T40S

Original BTs recorded by S. Truax in 1857, found as follows:

- White Oak snag, 24-inch diameter bears Record: $N8^\circ E$, 8.58 feet to estimated face. Re-measured 9.41 feet to center.
- The sprouted shell of 16-inch diameter white oak, containing reverse impression of scribed "1/" and partial "B" bears $S19^\circ W$, 53.46 feet on slope, to estimated face. Record, $S34^\circ W$, 53.46 feet. Re-measured 51.81 feet to center of tree.

I marked new trees C.S. BT and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 10-inch diameter bears $S29\frac{1}{2}^\circ E$, 26.39 feet.
- White Oak, 13-inch diameter bears $N54\frac{1}{2}^\circ W$, 42.86 feet.

Corner lies on South slope, in small rocky opening about, 100 feet diameter, surrounded by White Oak and Manzanita and about 20 feet West of draw C. $S20^\circ W$.

December 20, 1977
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor